



SOUTHWEST BUSINESS PRODUCTS LTD.

— From Bindings to Branding —



Triumph Cutter 5560LT

MARL5560LT

This MBM Triumph 5560LT 21½” Programmable Hydraulic Paper Cutter is equipped with a front and rear air tables. The 5560LT has a comprehensive SCS safety package: patented EASY CUT electronic blade activation bars for true two-hand operation; IR light beam safety curtain on front table; safety cover on rear table; lockable main switch; automatic blade and clamp return from every position; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine; blade and cutting stick can be changed without removing covers. Additional Features comes with: Hydraulic blade and clamp drive.



Easy to Use

Patented EASY CUT blade activation bars ensure true, two handed operation and allow blade and clamp to be activated independently.

HALIFAX NS
902.477.0382

MONTREAL QC
514.694.7741

OTTAWA ON
613.744.7004

TORONTO ON
416.285.7044

CALGARY AB
403.717.1707

VANCOUVER BC
604.574.9508



**SOUTHWEST
BUSINESS PRODUCTS LTD.**

From Bindings to Branding

5560LT

Triumph Cutter

Features

- Triumph 5560LT offers a high storage capacity, programmable EP back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements
- Programmable control unit features repeat cut and eject functions
- Up to 9 repeat cuts can be integrated into a program in a single step | Digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch)
- “Set” function key for reference measurement
- Self-diagnostic system with error indication displayed
- Electric, spindle-guided back gauge drive
- Electronic hand wheel with variable speed control for manual back gauge setting
- Bright, LED optical cutting line
- Precision swing-cut blade movement
- Hydraulic blade and adjustable hydraulic clamp drive
- The Triumph 5560 clamp is guided on both sides to apply even pressure along entire cutting width and is fully adjustable between 1,900 and 3,800 psi
- False clamp and foot pedal allows for pre-clamping

SPECS

Cutting Width	21 ⁵ / ₈ ”
Cutting Height	3 ³ / ₄ ” (3 ⁵ / ₈ ” with false clamp)
Narrow Cut	1 ¹ / ₄ ” (2 ⁵ / ₈ ” with false clamp)
Back Gauge	22 ⁷ / ₁₆ ”
Blade Drive	hydraulic
Clamp Type	adjustable hydraulic
Measurement	digital display (cm/inch)
Cutting Indicator	yes
Table Safety	IR light beam safety curtain
Blade Bars	yes
Tool Holder	yes
Accessories	front/read air tables
Dimensions	55” x 42” x 54”
Weight	1,014 lbs
Electrical Req.	115 V / 60 Hz
Motor Output	2 hp

HALIFAX NS
902.477.0382

MONTREAL QC
514.694.7741

OTTAWA ON
613.744.7004

TORONTO ON
416.285.7044

CALGARY AB
403.717.1707

VANCOUVER BC
604.574.9508