



SOUTHWEST BUSINESS PRODUCTS LTD.

— From Bindings to Branding —



FoilGlazer II Laminator & Foil Fuser

MARLFOILGLAZER2

Foilglazer II is a compact and robust laminating & foil fusing machine. It accommodates paper up to 14.3" x 23.6" in size. Ideal for laminating and embellishing digitally printed, short run jobs.



Automatic Air Suction Feeding

Foilglazer II can feed a wide variety of prints consistently. The feeder can take stocks from 110gsm to 400gsm in weight, as well as a variety of laminating films.

HALIFAX NS
902.477.0382

MONTREAL QC
514.694.7741

OTTAWA ON
613.744.7004

TORONTO ON
416.285.7044

CALGARY AB
403.717.1707

VANCOUVER BC
604.574.9508



**SOUTHWEST
BUSINESS PRODUCTS LTD.**

From Bindings to Branding

FoilGlazer II

Laminator & Foil Fuser

Features

- Operation is easy with the 4.3" color touch screen, with inching switch (forward/backward), and pressure roller lifting lever.
- The feeder can take stocks from 110gsm to 400gsm in weight, as well as a variety of laminating films commonly used in the markets, including films for digital print, soft touch films and anti-scuff films.
- Foilglazer II's feeder can be unfolded which makes film setting and regular maintenance easy.
- Using colored foil rolls, the machine can "foilglaze" (foil fusing) on black toners. This is an ideal way to add values on digital, short-run, on-demand applications.
- The maximum driving speed of the Foilglazer II is 16.4'/min. Thanks with the automatic film cutting mechanism, operator can walk away once the machine is started.
- Required compressor (not included):
 - Discharge amount more than .18 cfm
 - Tank capacity more than 1.1 gallon
 - Tube diameter 6mm OD, 4mm ID
 - Minimum pressure 0.6 MPa or 87 psi
- Usable Film (Laminating):
 - Width: 7.87" - 13.38"
 - Outer diameter: Up to 7.87"
 - Thickness: 20 - 45 micron
 - Core diameter: 1" or 3"
- Usable Film (Foilglazing)
 - Width: 12.44" - 13"
 - Outer diameter: Up to 2.36"
 - Core diameter: 1"

SPECS

Speed	Laminating: 16.4' /min. Foilglazing: 9.84' /min.
Sheet Capacity	2" stack
Paper Weight	110 - 400 gsm* (32lb bond - 150lb cover)
Paper Size	Laminating: 11.69" x 8.26" - 14.37" x 23.62" Foilglazing: 5.82" x 8.26" - 14.37" x 23.62"
Separation Method	Burst cutting
Power Supply	100-120 V, 50-60 Hz
Dimensions (W x D x H)	24.45" x 22.9" x 47.48" (main body) 24.45" x 67.6" x 47.48" (with tables)
Weight	254 lbs

*Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions.



HALIFAX NS
902.477.0382

MONTREAL QC
514.694.7741

OTTAWA ON
613.744.7004

TORONTO ON
416.285.7044

CALGARY AB
403.717.1707

VANCOUVER BC
604.574.9508